

DC1-1/DC4-1

13.56 MHz Clamshell Smartcard

Delta® Smartcard Technology
Data Sheet



Application - Ideal for access control applications such as door access.

Compatible - Can be encoded with 26-bit Wiegand, custom Wiegand or magnetic stripe formats.

Industry Friendly - Outputs CSN reads, Sector reads and can be ordered with custom encryption keys.

Convenience - Pre-punched slot makes it ideal to carry on a lanyard or badge holder.

Delta comprises Farpointe Data's 13.56 MHz line of contactless smartcard readers, cards and tags. Based upon proven MIFARE contactless digital radio frequency identification (RFID) technology, Delta readers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol. They offer value-add features such as MAXSecure™ and ValidID™, and support sector or CSN reads. Additionally, Delta cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered programmed to various formats and encryption keys.

©2012 Farpointe Data, Inc. All rights reserved. Farpointe Data, the Farpointe Data logo, Pyramid Series Proximity, Pyramid Series logo, Ranger and Delta are registered trademarks of Farpointe Data, Inc. MIFARE is a trademark of NXP Semiconductors. All other trademarks are the property of their respective owners.



TransTech Systems, Inc.
12142 NE Sky Lane, Suite 130
Aurora, OR 97002
Ph: 888-843-3643 Fax: 503-682-0166
sales@ttsys.com www.ttsys.com



DC1-1/DC4-1

13.56 MHz Clamshell Smartcard

Features and Specifications:

Technology:	Smartcard	Frequency:	Excitation (13.56 MHz)
Operation:	Passive (no battery)	Type:	Clamshell card
Formats:	Wiegand (26-bit and custom formats) and ABA Track II magnetic stripe (clock and data)	OEM Label Area Dimensions:	0.11 x 0.25 inch (2.9 x 6.6 mm), with corner radius of 0.63 inch (6.6 mm)
Dimensions (HxWxD):	3.4 x 2.2 x 0.06 inches (86 x 55 x 1.5 mm)	Operating Temperature:	-35° F to 122° F (-35° C to +50° C)
Material:	ABS	Weight:	0.3 oz. (9g)
Color:	Off-white	Humidity:	0-95% non-condensing
Slot Punch¹:	Standard, vertical slot	Marking²:	Date code and ID
Imaging³:	Use a glossy adhesive overlay for color dye sublimation printing or print directly on card	Warranty:	Limited lifetime warranty
Read Range⁵:	Up to 3 inches (76 mm)	Options⁴:	Custom printing of company logos, URL, telephone number and more
Outputs⁶:	CSN and Sector	Memory:	DC1-1: 1K memory DC4-1: 4K memory
ISO Standards:	Technology: ISO 14443 Size: N/A		

¹ Models DM1-3, DM4-3, DM1-3S and DM4-3S may be ordered pre-punched with horizontal/vertical slots. Contact Farpointe or your supplier for more information.

² Matching internal and external sequential coding standard. Custom printing available.

³ Please verify that the printer (or overlay) supports credential type/thickness.

⁴ Contact Farpointe to learn how you can customize your cards and tags.

⁵ Tested with 12VDC @ Delta5 reader. Reference Card Read Range Document for additional read range information.

⁶ CSN = Card Serial Number. Sector = access control data, such as format, facility code and ID.

Farpointe Data reserves the right to change specifications without notice.



TransTech Systems, Inc.
12142 NE Sky Lane, Suite 130
Aurora, OR 97002
Ph: 888-843-3643 Fax: 503-682-0166
sales@ttsys.com www.ttsys.com

