

P-900

125 kHz Proximity Card Reader

Pyramid Series Proximity®
Data Sheet



Application - High performance design makes it ideal for longer range applications such as door access (metal or plastic wall-box mount or parking bollards), gate entry and parking barriers.

Compatible - Wiegand and magnetic stripe protocols for easy integration with standard access systems.

Industry Friendly - Can support several proximity card and tag technologies.

Performance - Delivers non-contact read ranges up to 20 inches (508 mm).

Durable - Electronics are secured with tamper- and weather-resistant epoxy potting, and backed by a lifetime warranty.

Pyramid Series Proximity from Farpointe Data sets the electronic security benchmark for 125 kHz proximity readers, card and tags. Based upon proven contactless digital radio frequency identification (RFID) technology, Pyramid readers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol. They offer value-add features such as MAXSecure™ and fleaPower™, and can be ordered to support several proximity card and tag technologies. Additionally, Pyramid cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered to support several proximity reader technologies.

©2012 Farpointe Data, Inc. All rights reserved. Farpointe Data, the Farpointe Data logo, Pyramid Series Proximity, Pyramid Series logo, Ranger and Delta are registered trademarks of Farpointe Data, Inc. Mifare is a registered trademark of NXP Semiconductors. AWID is a trademark of Applied Wireless Identifications Group. HID and the HID logo are registered trademarks of HID Global Corporation, an ASSA ABLOY company. All other trademarks are the property of their respective owners.



TransTech Systems, Inc.
12142 NE Sky Lane, Suite 130
Aurora, OR 97002
Ph: 888-843-3643 Fax: 503-682-0166
sales@ttsys.com www.ttsys.com



P-900

125 kHz Proximity Card Reader

Pyramid Series Proximity® Data Sheet

Features and Specifications:

Technology:	Proximity	Frequency:	125 kHz
Mounting:	Metal or plastic US single-gang/double-gang wall box, as well as standard parking bollards and non metallic flat surfaces	Dimensions (HxWxD):	10.5 x 10.5 x 2 inches (267 x 267 x 51 mm)
OEM Label Area Dimensions:	N/A	Weight:	37.4 oz. (1060g)
Certifications:	FCC, ICC, CE	IP Code:	IP67 ⁴
Voltage²:	+5 - 16 VDC	Current Draw:	290 mA typical, 500 mA peak @ 12VDC
Read Range³:	Up to 20 inches (508 mm)	Cabling⁵:	24 AWG minimum, multi-conductor stranded with an overall foil shield
Interface:	Wiegand ABA Track II	Operating Temperature:	-40° F to 149° F (-40° C to +65° C)
Color Options:	Black enclosure with a black label concealing mounting screws	Audio Tone:	Beeper included standard
Indoor & Outdoor Installation:	Electronics sealed in weather- and tamper-resistant epoxy potting	Warranty:	Limited lifetime warranty
LED:	Four-state standard (red, green, amber & off)	Keypad Output⁶:	N/A
Technologies Supported:	P-900: Pyramid Series Proximity Cards and Tags ⁷ P-900-H: Pyramid + certain HID® Proximity protocols ⁸ P-900-A: Pyramid + certain AWID® 125-kHz Proximity protocols ⁹ P-900-H-A: Pyramid + certain HID 125-kHz Proximity protocols + certain AWID 125-kHz Proximity protocols		

² Linear power supplies are recommended for best operation; recommended models - Altronix LPS3C12X, Electronic Security Devices LP1EST12, Highpower Security Products Lightning 505.

³ Using PSC-1 Standard Light Proximity Card with 12VDC at the reader.

⁴ Self evaluated

⁵ For example Belden 9535 or similar.

⁶ Available only on P-640 models; 8-Bit Burst or 26-bit Wiegand standard, for 4-Bit Burst and other options please contact Farpointe.

⁷ Examples may include, and may not be limited to, PSC-1, PSI-4, PSM-2, PSK-3, and PDT-1.

⁸ Examples may include, and may not be limited to, ProxCard® II, ISOProx® II and ProxKey® II.

⁹ Examples may include, and may not be limited to, CS Prox Card, GR (ISO) Graphics Quality Prox Card and KT Key Tag.

Farpointe Data reserves the right to change specifications without notice.



TransTech Systems, Inc.
12142 NE Sky Lane, Suite 130
Aurora, OR 97002
Ph: 888-843-3643 Fax: 503-682-0166
sales@ttsys.com www.ttsys.com

